


DVR

8/16CH Hybrid DVR



TD-2700BE-HP



TD-2700BE-HP series supports 8MP / 5MP / 4MP / 3MP / 1080P / 720P / WD1 analog and IP video input simultaneously. It adopts the standard H.265 high profile compression format and the most advanced SOC technique to ensure real time recording in each channel and realize outstanding robustness of the system.

TD-2700BE-HP series supports 8 / 16 CH video input and 8 / 8 CH audio input, simultaneous 8 / 16 CH playback. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.




en.tvt.net.cn

For more information, please visit our website

Features


- 8 / 16 CH TVI / AHD / CVI 8MP / 5MP / 4MP / 3MP / 1080P / 720P / WD1 video input
- 8 / 16 CH DVRs support 8 / 8 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input by default
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-type recording: manual / schedule / sensor / motion / analytics recording
- Playback : 8 / 16 CH simultaneously playback
- Search: time slice, time, event, tag and smart search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Authorization management, log review and device status review
- HDMI 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

Dimensions




Rear Panel

TD-2708BE-HP



TD-2716BE-HP



Specifications

| Model | | TD-2708BE-HP | TD-2716BE-HP |
|--------------------------|--|--|-----------------------|
| System | OS | Embedded Linux | |
| Video | Analog Video Input | BNC × 8 | BNC × 16 |
| | | BNC interface (1.0Vp-p; 75Ω) | |
| | | TVI/AHD/CVI: 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P/WD1@30fps (live) | |
| | IP Video Input | 8CH (up to 16CH) | 8CH (up to 16CH) |
| | | Up to 8MP@30fps | |
| | Total Input | 16CH | 24CH |
| | Output | HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 BNC × 1 : CVBS (used as the main or spot output) | |
| Compression | H.264/H.265 | | |
| Multi-screen Display | 1/4/6/8/9/16 | 1/4/6/8/9/13/16/25 | |
| Audio | Input | RCA × 8 | |
| | Output | RCA × 1 (linear, 600Ω) | |
| | Two-way audio | Take up channel one audio input | |
| | Compression | G.711(U/A) | |
| Record | Resolution | 4K/4K Lite/5MP/5MP Lite/4MP/4MP Lite / 3MP/1080P/720P/WD1/D1 | |
| | Frame Rate | Analog Channel: 4K@8fps (PAL/NTSC) 4K Lite@12fps/15fps (PAL/NTSC) 5MP@12fps (PAL / NTSC) 5MP Lite@20fps (PAL / NTSC) 4MP/3MP@12fps/ 15fps (PAL / NTSC) 4MP Lite/1080P/720P/WD1/D1@25fps/30fps (PAL / NTSC) IP Channel: 25fps / 30fps (PAL / NTSC) | |
| | Bit Rate | 32Kbps ~ 8Mbps | |
| Playback | Playback | 8CH | 16CH |
| | Search | Time slice / time / event / tag / smart search | |
| | Smart Search | Highlight colors to display the camera record in a certain period of time, different colors refer to different record events | |
| | Function | Play, pause, FF, FB, digital zoom, etc. | |
| Alarm | Mode | Manual, motion, exception, smart event | |
| | Input | 8CH | 16CH |
| | Output | 2CH | 4CH |
| Network | Interface | RJ 45 1000Mbps × 1 | |
| | Protocol | TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP | |
| | Incoming Bandwidth | 32Mbps | |
| | Outgoing Bandwidth | 96Mbps | |
| | Client Connection | Max. 10 users access | |
| MobileDevice | OS | iOS, Andriod | |
| Storage | HDD | SATA× 2, up to 10TB per HDD; E-SATA× 1 | |
| Backup | Local Backup | U disk, USB mobile HDD | |
| | Network Backup | Yes | |
| Port | RS 485 | Yes (half-duplex), connect to PTZ or keyboard | |
| | USB | USB 2.0 × 1; USB3.0 × 1 | |
| | Remote Controller | Optional | |
| Others | Power Supply | DC12V / 4A | |
| | Consumption | ≤ 15W (without HDD) | ≤ 30W (without HDD) |
| | Dimensions(mm) | 380 × 268 × 45 (W × D × H) | |
| | Working Environment | -10~50°C, 10%~90% (humidity) | |
| | Certificate | CE, FCC | |
| Environmental Protection | Comply with Directive EU RoHS, WEEE, REACH | | |